

Beam stacking experiment proposal at KURNS 23/06/22

J.B. Lagrange On behalf of IBG, ISIS, RAL, STFC

FETS-FFA questions

Beam stacking questions for FETS-FFA:

- Whow many protons can we accumulate without beam loss by beam stacking at top energy?
- How many protons can we capture and extract without beam loss after beam stacking?

Note: "without beam loss" to be defined later (e.g. 5%, 1%, or 0.1%).



Demonstration of concept at KURNS

- Stack 2 beams
- Measure the effect of accelerating beam/RF bucket on stacked beam



Main Ring parameters

Radius	4.54 m
RF frequency	1.6 ~ 5.2 MHz
Revolution time	$0.625 \sim 0.192 \ \mu s$
Beta (11 MeV, 18 MeV)	0.1518, 0.1931 (ratio=1.27)
Beta (11 MeV, 47 MeV)	0.1518, 0.3052 (ratio=2.01)
Beta (0.4 GeV, 1.2 GeV)	0.7131, 0.8986 (ratio=1.26)



Experiment proposal

3 Steps:

- 1. Coasting beam characterisation: 1 week
- 2. Measurement of interference of empty bucket (accelerating RF without beam): 1 week
- 3. Measurement of stacked beam: 1 week



One bunch only

Subject	Preparation	Measurements
Debunch adiabatically the 1st bunch	• Determine RF profile (frequency and voltage) to minimise $\Delta p/p$ after debunch	 Δp/p measurement Transverse beam profile measurement
Rebunch the coasting beam	 Determine RF profile (frequency and voltage) to minimise longitudinal emittance 	 Beam intensity measurement Longitudinal tomography measurement Transverse beam profile measurement
Repeat debunch and rebunch process	• Same as above	• Beam intensity, $\Delta p/p$ increase at debunch, longitudinal emittance increase at rebunch and transverse beam profile increase vs. the number of process



Momentum spread measurement

- Bunched beam: longitudinal tomography
- Coasting beam?
 - Measure of beam size, with known dispersion (D=0.53 m)
 - O Possible if $\Delta p/p \cdot D$ (~1 cm) >> beam size
 - Emittance of the beam after injection (i.e. ~100 hits on foil)?




Coasting beam and empty bucket

Subject	Preparation	Measurements
After debunching at E1, increase RF voltage with frequency at several points between injection and E1.	 Simulation to see how the coasting beam is affected. When E1 is increased and RF frequency ratio approach 2, how quickly interference grows? 	 Δp/p measurement vs time (time scale should be determined by simulation) Transverse beam profile measurement
Increase the energy of an empty bucket and adiabatically decrease voltage as if the beam is accelerated and debunched.	 Simulation to see how the coasting beam is affected. 	 Δp/p measurement Transverse beam profile measurement
(optionally) rebunch the coasting beam	Same with one bunch	 Beam intensity measurement Longitudinal tomography measurement Transverse beam profile measurement





Setting up



- "accelerate" an empty bucket either with h=1 or 2 RF frequency.
 - phis = 20 degree, voltage = 4 kV.
- RF frequency with h=2 at injection.
 - h=2 at ~11 MeV
 - h=1 at ~55 MeV (not at 44 MeV due to horizontal excursion.)









Effects on coasting beam at injection energy (11 MeV)

(S. Machida)



Effects on coasting beam at higher energy (55 MeV)

(S. Machida)



Revised plan

- Normal operation of KURNS main ring does not show interference
- accelerate an empty bucket of h=2 to E2<E1
- Hopefully enough shunt impedance of the cavity to 2x3.2 MHz (normal range of RF frequency 1.6 to 5.2 MHz)
- To demonstrate beam stacking of 2 beams, is it possible to capture and accelerate the beam with h=2 from injection?



Schedule

- Reasonable date for IBG members would be next winter (January, February 2023)
- Proposal from Ishi san: 10/01/23 to 27/01/23

